

Two Stage Electric - Single Phase



216V



318VLE



318H



Model	Part #	HP	Voltage/ Phase	Tank (Gal)	ACFM @ 100 psi	ACFM @ 175 psi	Max Pressure	Dim. In. L X W x H	Shipping Weight
216V	8090250002	5	208-230/1	60V	15.33	13.75	165 psi	29 x 20 x 68	348 lbs
218V	8090250004	5	208-230/1	80V	15.33	13.75	175 psi	39 x 24 x 73	382 lbs
218H	8090250003	5	208-230/1	80H	15.33	13.75	175 psi	71 x 24 x 45	412 lbs
318VN	8090250017	5	208-230/1	80V	18.50	16.60	175 psi	39 x 24 x 77	428 lbs
318HN	8090250012	5	208-230/1	80H	18.50	16.60	175 psi	71 x 24 x 49	468 lbs
318V	8090250013	5	208-230/1	80V	18.50	16.60	175 psi	39 x 24 x 77	457 lbs
318H	8090250008	5	208-230/1	80H	18.50	16.60	175 psi	71 x 24 x 49	491 lbs
318VE	8090250014	5	208-230/1	80V	18.50	16.60	175 psi	39 x 24 x 77	467 lbs
318HE	8090250009	5	208-230/1	80H	18.50	16.60	175 psi	71 x 24 x 49	501 lbs
318VL	8090250015	7.5	208-230/1	80V	25.25	22.28	175 psi	39 x 24 x 77	479 lbs
318HL	8090250010	7.5	208-230/1	80H	25.25	22.28	175 psi	71 x 24 x 49	538 lbs
318VLE	8090250016	7.5	208-230/1	80V	25.25	22.28	175 psi	39 x 24 x 77	477 lbs
318HLE	8090250011	7.5	208-230/1	80H	25.25	22.28	175 psi	71 x 24 x 49	491 lbs

Magnetic Starter Standard or Not Required on 216V, 218V, 318VN, 318VL, 338VL and equivalent Horizontal Models.

Standard Features

- Solid Cast Iron Cylinder
- Start-Stop Pressure Switch Control
- ASME Code Tank and Safety Valves
- Fully Enclosed High Flow Belt Guard
- Oil Level Sight Glass
- 100% Factory Tested at Full Pressure
- 208-230 Volt Motors
- 2 Year Bumper to Bumper Warranty

All "Elite Series" Compressors include Magnetic Starter, Low Oil Switch, Automatic Tank Drain, and Triple Pass Pump Mounted Aftercooler.